

ACRYLIC WOOD PRIMER UNDERCOAT

*Water Based

*Low Odour

*Non Flammable

Description: A high performance primer undercoat specially formulated on a water thinnable emulsion resin. Suitable for interior or exterior application, Acrylic Wood Primer Undercoat has been designed to drastically reduce the expensive recoating time factor which is so important to the Decorator and Painting Contractor.

Uses: Suitable for use on most non metal surfaces such as timber, plaster, hardboard, building boards, cement and brickwork after suitable preparation. Ideal for the factory priming of joinery.

Preparation: Surfaces must be sound, clean, dry and free from wax, grease and oil. Remove all dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Any bare surfaces should be primed with a first coat.

Application: Stir thoroughly and check colour before use. Apply by brush, medium or short pile roller or spray. Ensure adequate ventilation during application and drying. Do not apply at temperatures below 8°C, or when raining or foggy.

Coverage: Approximately 11 - 13 sq. metres/litre, depending on porosity of the substrate.

Drying: Normally 1 hour @ 18° Centigrade and 65% humidity.

Recoatable: After 2 hours, enabling the second coat to be applied to fulfil the function of an undercoat. After a further 2 hours, the final gloss coat can be applied enabling a three coat painting system to be completed in one day.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Pack sizes: 2.5 litre, 5 litre, 25 litre

Storage: Keep out of reach of children. Protect from frost.

Colour Range: White. Other colours made on request.